

DIMENSIONS & TOTAL AXLE WEIGHTS

		DIMENSIONS		CONDITIONS	NOTES & ADDITIONAL CONDITIONS
		LEGAL (Section 110)	SF ANNUAL		
WIDTH (m)	2.6m	3.66m	3.66m - 3.99m	No conditions	S.F.. Lane width is 3.25m average Clear Hamlets if tight. No more than 5min. road closures Consider time of day (buses, commute times, safety when approving)
			4.0m - 4.59m	Applicant to provide own front escort	
			4.60m - 4.99m	Applicant to provide own front and back escort	
			5.0m – 5.9m (superload)	Applicant to provide a minimum of three escort vehicles, (two shall be MTO certified superload escorts). *Copy of the escort certification required before issuing permit*. Continue to allow OPP escorts as an alternative during transition	
			6.0m-6.9m (superload)-	Applicant to provide a minimum of four escort vehicles, (two shall be MTO certified superload escorts). *Copy of the escort certification required before issuing permit* Continue to allow OPP escorts as an alternative during transition The maximum road segment that shall be closed at any one time is 3 km and all traffic in that segment shall be cleared before he next segment is closed	
			>7.0m (superload)	Applicant to provide a minimum of five MTO certified superload escorts *copy of the escort certification required before issuing permit* Continue to allow OPP escorts as an alternative during transition Applicant to submit a Traffic Management Plan (TMP level 3 per MTO requirements) a minimum of two weeks prior to the move. The maximum road segment that shall be closed at any one time is 3 km and all traffic in that segment shall be cleared before he next segment is closed	
LENGTH (m)	12.5m (single) 23m (combination)	25m	25.1m-29.9m	Applicant to provide own back escort A minimum speed of 30 km/hr shall be maintained when crossing railway tracks and adequate distance shall be maintained in front of truck in order to clear railway tracks without having to stop". - Contact Rail Companies prior to move:	
			30.0m-45.75m	Applicant to provide own front and back escort Same railway condition as above (if crossing RR's)	
			>45.75m (superload)	Applicant to provide a minimum of three escort vehicles, (two shall be MTO certified superload escorts). *Copy of the escort certification required before issuing permit* Continue to allow OPP escorts as an alternative during transition	
HEIGHT (m)	4.15m	4.4m	4.4m - 4.59m	Responsible for clearing overhead utilities	Utilities are supposed to be 4.7m above road
			4.60m +	Responsible for notifying utility companies and for clearing overhead utilities	
WEIGHT (kg)	1 axle	9,000	10,000	Must make special application	Can approve to a maximum of 15% over legal on Twp Roads . Check what maximum weight on road section has been permitted over past calendar year. Allow ¾ loads during half load season for feed (~7.5 tonnes/ axle)
	2 axle group	18,000	19,500		
	3 axle group	25,500	27,500		
	4 axle group	Depends on configuration	~10% over legal		
At >120,000kg total gross weight, it is a "superload" and the company must do a TMP level 1 and bridge review					